



Content

.....

algorithms

Validation

Test Scene Results

Summan

EarthCARE BBR Fluxes evaluation using test scenes

A. Velázquez Blázquez¹, E. Baudrez¹, N. Clerbaux¹ C. Domenech², R. García Marañón

¹Royal Meteorological Institute of Belgium (RMIB) ²GMV Aerospace and Defence, Spain

October 12-14, 2022

2022 Earth Radiation Budget Workshop



Content

Introduction

Flux conversion

Validatio

Test Scene Results

Summa

Content Introduction

The EarthCARE mission

EarthCARE Production Model

BBR Configuration

Integration areas
Flux conversion algorithms

BBR Reference Level

Validation

Test Scenes Results

Halifax

Baja

Hawaii



Credit: ESA P. Carril, 2013



▶ EarthCARE is the sixth Earth Explorer Mission of the ESA Living Planet Program. (Scheduled for launch in 2023/2024)

 Objectives: Improve understanding of cloud-aerosol-radiation interactions so as to include them correctly and reliably in climate and NWP models

EarthCARE Payload Atmospheric Lidar (ATLID) 355 nm (UV) with depolarization channel High spectral resolution capability providing direct cloud/aerosol extinction measurements Broadband Radiometer (BBR) SW & TW 3 views to get fluvos Cloud Profiling Radar (CPR) 94 GHz Min detectable signal -35 dBZ Multispectral Imager (MSI) 4 solar and 3 thermal infrared channels 150-km swath

- ► EarthCARE radiative mission requirement: constrain retrievals of cloud and aerosol properties defined by the active sensors such that TOA radiative fluxes are accurate to within 10Wm⁻²
- ► Orbit: Sun-synchronous, DN 14:00 Height: 393 km mean spherical altitude (394.4km for cal/val orbit)

- A. Velázquez et al.
- Content

Introduction

The EarthCARE mission

EarthCARE Production Mode BBR Configuration Integration areas

Flux conversion algorithms

Validation

Test Scene

Content

Introduction

The EarthCARI

EarthCARE Production Model


BBR

Integration areas

Flux conversion algorithms

Validatio

Test Scene Results



Content

Introduction

The EarthCARI


EarthCARE Production Model

Configuration

Flux conversion

/alidatio

Test Scen Results



Content

Introduction

The EarthCARI

EarthCARE Production Model


Configuration

Integration area

Flux conversion algorithms

/alidatic

Test Scen Results






Configuration

Integration areas


- BBR Configuration
 Along track sampling: 3 telescopes (nadir 0° , fore $+55^{\circ}$, aft -55°)
 - ► Two spectral channels:


SW
$$(0.2 - 4 \mu m)$$

TOT $(0.2 - 500 \mu m)$



Radiometric accuracy:









Content

Introduction

The EarthCARE mission EarthCARE Production Model

Configuration
Integration areas

algorithms

Validatio

Test Scene Results

Summary

► On BBR grid:

- ► 10×10km²: Standard resolution
- ▶ 5×10km²: Small resolution
- Full swath x10km²: Full resolution (no combined flux)
- On Joint Standard Grid (JSG):
 - 5 x 21 JSG pixels: assessment domain (configurable)

	Full speed					
Nadir						
Oblique						

10km along track integration

Notes : - all regions sampled @ 1km - dimensions are configurable




BBR Flux estimation

BBR measure radiances $L(\theta, \phi)$ [Wm⁻²sr⁻¹] at the TOA but flux is

$$F = \int_{ heta=0}^{rac{\pi}{2}} \int_{\phi=0}^{2\pi} L(heta,\phi) cos(heta) sin(heta) d heta d\phi$$

Need of Angular Dependency Models (R)

$$F = \frac{\pi L(\theta, \phi)}{R(\theta, \phi)}$$



In the LW:
$$R(\theta) = a_0 + a_1 \cdot z_1 + a_2 \cdot z_2 + a_3 \cdot z_1^2 + a_4 \cdot z_1 \cdot z_2 + a_5 \cdot z_2^2$$
$$z_1 = BT_{10.8 \mu m}, z_2 = BT_{12 \mu m} - BT_{10.8 \mu m}$$

- Need a geophysical database to obtain ai: Use of SITS Database
- BBR 3 views flux is estimated as:

$$F = \frac{1-lpha}{2}(F_{ extsf{fore}} + F_{ extsf{aft}}) + lpha F_{ extsf{nadir}}$$

Flux conversion algorithms

Content

Introduction

Flux conversion algorithms BBR Reference Level

Validation

Test Scenes

Summary

► In the SW:

ADMs are feed-forward back-propagation artificial neural networks Need a geophysical database for network training:


- CERES flux/radiance (SSF Ed. 4)
- ► ERA-20C
- MODIS albedo climatology
- AERONET climatology
- BBR 3 views flux is estimated as:

$$\overline{F}_{SW} = \frac{1}{\varepsilon_{N}} \left(\frac{1}{\varepsilon_{Faft} \varepsilon_{Raft}} F_{aft} + \frac{1}{\varepsilon_{Fnad} \varepsilon_{Rnad}} F_{nad} + \frac{1}{\varepsilon_{Ffore} \varepsilon_{Rfore}} F_{fore} \right)$$

If fractional error is below a threshold, flux estimates are averaged by weighting the fluxes by their estimated error and the radiometric performance of every view

BBR Reference Level

- Important to define Flux reference level for the collocation of the views to avoid parallax
- LW: The reference level will be placed at the altitude of the highest cloud in the footprint (using statistics on the MSI cloud top height product in nadir)
- SW: Views are co-registered at a RL defined as the vertical level in the atmospheric nadir domain that minimizes the flux differences between the nadir, aft and fore flux retrievals




- A. Velázquez et al.
- Content
- Introduction
- algorithms

Validation

Results

- ▶ Study based on CERES TAT data, allowing to estimate the true flux (Direct Integration)
- Best weigthing using real data: $\alpha \sim 1/3$
- ▶ 3D effects are important and the three views should be considered




LW: Regional Analysis Validation

Comparisons of GERB/BBR-like data with collocated CERES - March 2004



Validation



(1) Mean CERES Flux March 2004. $F_{BBR-like}$ vs $F_{CERES}(Wm^{-2})$

	GERB 4 LibRadtran + SBDART	GERB 4 Ed-1 SBDART	BBR 2 BT Improved DB bins 20 W m ⁻²
Nadir	6.9	7.9	6.1
Off-nadir	7.6	7.6	7.7
0<60	7.6	7.8	7.2

(2) Mean GERB/BBR Flux March 2004



240



LW: Theoretical ADM's applied to CERES SSF Ed-3A data March

A. Velázquez et al.


Content

Introductio

Flux conversion

Validation

Results




- (1) All viewing zenith angles. $RMS = 2.75Wm^{-2}$
- (2) Nadir (θ < 5). $RMS = 3.56Wm^{-2}$
- (3) Off-nadir (50 $< \theta <$ 55) $RMS = 0.98Wm^{-2}$

LW: Theoretical ADM's applied to CERES EBAF data Dec 2005

A. Velázquez et al.

Validation





SW: Sample of validation over ocean using CERES data

A. Velázquez et al.

Validation




Figure 20 Density scatter plots of the SW anisotropic factors estimated with the nadir BMA-FLX SW model and the CERES-derived fluxes for (bottom) cloudy MCL ocean, (left up) cloudy OVC ocean and (right up) cloudy PCL ocean scene classes.

Sky conditions	ADM	RMS (W m ⁻²)	CVRMS (%)	P ₃₃ (MAE) (W m ⁻²)	P ₆₆ (MAE) (W m ⁻²)	P ₉₉ (MAE) (W m ⁻²)	Samples
clear-sky	nadir	4.21	2.14	0.87	2.42	14.28	3618993
	forward	4.12	1.86	0.81	2.28	14.28 15.35	856146
	backward	4.22	2.23	0.88	2.37	15.38	808108
cloudy-sky	nadir	6.05	2.23	1.48	3.99	20.77	17601681
	forward	5.30	2.09	1.50	3.73	18.31	7402302
	backward	4.31	1.89	1.23	2.98 3.71	15.42 19.97	7369598
all-sky	nadir	6.05 5.30 4.31 5.78	2.34	0.87 0.81 0.88 1.48 1.50 1.23 1.34	3.71	19.97	21220674
	forward	5 19	2.08 1.92	1.40	3.60 2.93	18.03	8258448
	backward	4.30	1.92	1.19	2.93	15.42	8177706



Content

Introduction

Flux conversional algorithms

Validatio

Test Scenes Results Halifax

Halifax Baja Hawaii

- Three test scenes have been created by EC and KNMI by applying instrument simulators to the model data from the Global Environmental Multi-scale (GEM) NWP model.
- ▶ The resulting estimates go into radiative transfer models that produce top of atmosphere solar and thermal radiative quantities.
- ▶ The test frames are 6200 by 200 km with horizontal resolution of 250m and 57 vertical layers.
 - ▶ Halifax: Greenland to The Caribbean crossing a cold front
 - Baja: Nunavut to Baja California over the Rocky Mountains
 - Hawaii: central equatorial Pacific Ocean including a mesoscale convective system

Content

Introduction

algorithms


Validation


Test Scene

Halifax

Baja ..

Summary







This case includes Sun just below the horizon over Greenland, cold air over Labrador, a cold-front near Halifax, dense overcast south of Halifax, and scattered shallow convection south of Bermuda

Content

Introduction


algorithms


Validation

Test Scene

Halifax Baja

Summary





This case includes Sun just below the horizon over Greenland, cold air over Labrador, a cold-front near Halifax, dense overcast south of Halifax, and scattered shallow convection south of Bermuda

Content

Introduction


algorithms

Validatio

Test Scene Results

Baja

Summar



This case includes clear and cold conditions at the northern extremity, scattered cloud through the Canadian Prairies, overcast over the Rocky Mountains, clear through Utah, and cirrus in Arizona and Mexico.

Content

Introduction


algorithms

Validatio

Test Scene Results

Baja

Summar



This case includes clear and cold conditions at the northern extremity, scattered cloud through the Canadian Prairies, overcast over the Rocky Mountains, clear through Utah, and cirrus in Arizona and Mexico.

Content


Introduction

algorithms

Validatio

Test Scene Results Halifax Baja

Hawaii Summary



Central equatorial Pacific Ocean including a mesoscale convective system

Content

Introduction

Flux conversion algorithms

Validatio

Test Scene Results

Baja

Hawaii

BMA -FLX thermal combined ton-of-atmosphere flux date: 20220923 Creation date: 10/10/2022 15:49:43 scene: HAWAII (42043E) - Processor version: v10.0 surface cover Resolution: StandardResolution classification Overcast - true flux hawaii - lw true flux BMA -FLX Latitude [°] BMA_-FLX thermal combined top-of-atmosphere flux vs. RT true flux date: 20220923 Scene: HAWAII - Processor version: v10.0 Resolution: StandardResolution Earth CARE orbit (20220E) MODIS(500 m), radiance (459-479 nm), Gridded around 00:50 UTC -27.81 -22.29 -16.76 -11.24 -5.72 -0.19 5.33 10.85 16.38 21.89 Ordeide of the MODIS field of view — mean mean diff = -1.5696 [Wm⁻²] DMSE std = 5.5864 [Wm-2]

· BMA -FLX - RT true flux

20 10 0 10 -10 -20 Central equatorial Pacific Ocean including a mesoscale convective system

RMS = 5.8027 [Wm⁻²]

Content

Introduction

algorithms

Validatio

Test Scene Results

- A radiance to flux conversion algorithm has been developed for the BBR
- Estimated performance:
 - LW: Nadir $\sim 3.5Wm^{-2}$, off-nadir $\sim 1Wm^{-2}$ for plane-parallel scenes $\sim 7Wm^{-2}$ for 3D scenes
 - ▶ SW: $\sim 15Wm^{-2}$ for the combined flux
- L2 processors have been chained and been verified using test scenes.
- Algorithms are documented in the ATBD
- LW ADMs to be used in GERB Ed-2 LW Flux
- For more information see:
 - BAMS Article: The EarthCARE Satellite. August 2015
 - AMT Special Issue on EarthCARE L2 algorithms and data products to come in 2023.
 - JAXA EarthCARE Pre-Launch Science and Validation Workshop 2023 (9-13 October 2023, ESA-ESRIN, Italy)

